

## Ruggedized MCS Cable 4'000 A

### Application: MCS Couplers for Electric Vehicles

The Grivix 4,000A MCS Cable facilitates direct current (DC) charging at up to 4,000 amperes (max. 6 Megawatt) using a sophisticated cooling system. Compatible with MCS vehicle inlet connectors (EV), for installation in electric charging stations (EVSE). It requires an additional cooling unit. Additionally, its design is tailored for customization, making it ideal for small-scale, client-specific applications.



### Benefits

- Capable of high currents.
- Adaptable for small series.
- Precisely manufactured in Switzerland.
- Increased IP rating
- Ready for harsh environments.

### Product Definition

Product Type	MCS Cable
Standards	IEC 63379, CharIn Ruggedized MCS Whitepaper
Ingress Protection	IP66 (mated), IP20 (unmated)
Conformance	CE compliant

### Electrical Data

Maximum operational voltage	1'500 V <sub>DC</sub>
Maximum operational current	4'000 A
Thermal Monitoring	2x Pt 1000
Power Contacts	DC+, DC-, PE
Signal Contacts	CP, PP, Comm 1, Comm 2

### Mechanical Data

Material	PA 12 / Copper / Aluminium
----------	----------------------------

### Environmental Data

Operating temperature range	-35 °C to +50 °C
-----------------------------	------------------



Maximum temperature	110 °C
RoHS compliant	

## Product Range

Description	Length	Weight [kg]
Ruggedized MCS Cable 3 m	3 m (2 m + 1 m)	
Ruggedized MCS Cable 4 m	4 m (3 m + 1 m)	16.45 kg
Ruggedized MCS Cable 5 m	5 m (4 m + 1 m)	
Ruggedized MCS Cable 6 m	6 m (5 m + 1 m)	28.30 kg

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

DO NOT COPY WITHOUT WRITTEN APPROVAL